



## 7Kw 32A Home Electric Car AC Type2 Portable EV Charging Stations For Electric Vehicles

Our Product Introduction

for more products please visit us on [evstationcharger.com](http://evstationcharger.com)

### Basic Information

- Place of Origin: China
- Brand Name: MINKO
- Certification: CE(ICR lab), UKCA, ROHS ISO, REACH
- Model Number: VPC-62-32AC
- Minimum Order Quantity: 5 pieces
- Price: negotiation
- Packaging Details: L210xW85xH52 (mm)
- Delivery Time: 8 -10 working days
- Payment Terms: T/T, Western Union, MoneyGram, Paypal, Skrill, Transferwise
- Supply Ability: 1000000 pieces per month




### Product Specification

- Charging Plug: IEC 62196 Type 2
- Rated Voltage: AC 200-250V
- Rated Current: 32A
- Rated Power: 7kW
- Input Power: 250V Max
- Operating Temperature: -35°C To 50°C
- Start Method: Plug And Play
- Electric Cable: IP65 Circuit Breaker
- Highlight: 7kw portable ev car charger, IEC 62196 3 phase portable ev charger, 32a 3 phase portable ev charger



### More Images



## Product Description

### 7Kw 32A Home Electric Car AC Type2 Portable EV Charging Stations For Electric Vehicles

#### Detailed specification:

Portable EV Charger, with power ratings of 3.5KW, 7 kW, is suitable for different types of vehicles.

Adjustable current, suitable for various scenarios.

The Voltage and Current are stable during charging, which can protect the battery and delay using time.

We can use normally in ultra-high temperature environment up to 50 .

It can also be used normally in the -35 .

|                         |                                                                                                                                                                                                                                                                                                                                              |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Charging plug           | IEC 62196 Type 2                                                                                                                                                                                                                                                                                                                             |
| Model No.               | VPC-62-32AC                                                                                                                                                                                                                                                                                                                                  |
| Rated voltage           | AC 200-250V                                                                                                                                                                                                                                                                                                                                  |
| Rated current           | 32A                                                                                                                                                                                                                                                                                                                                          |
| Rated power             | 7kW                                                                                                                                                                                                                                                                                                                                          |
| Certificates            | CE(ICR lab), UKCA, ROHS,ISO, REACH                                                                                                                                                                                                                                                                                                           |
| Protection rank         | IP54 cable; IP65 circuit breaker                                                                                                                                                                                                                                                                                                             |
| electric cable          | IP65 circuit breaker                                                                                                                                                                                                                                                                                                                         |
| LCD                     | 2.8" LCD screen                                                                                                                                                                                                                                                                                                                              |
| LED indicator           | Blue/Red/Green                                                                                                                                                                                                                                                                                                                               |
| Earth leakage protector | 30m AC                                                                                                                                                                                                                                                                                                                                       |
| input power             | 250V Max                                                                                                                                                                                                                                                                                                                                     |
| length                  | 5m or customized                                                                                                                                                                                                                                                                                                                             |
| Package Size            | L210xW85xH52 (mm)                                                                                                                                                                                                                                                                                                                            |
| start method            | Plug and Play                                                                                                                                                                                                                                                                                                                                |
| Operating temperature   | -35°C to 50°C                                                                                                                                                                                                                                                                                                                                |
| electrical protection   | Overcurrent protection, residual current protection, grounding protection, surge protection, Overvoltage/undervoltage protection, overvoltage/underfrequency protection, overtemperature protection                                                                                                                                          |
| Applied Materials       | Housing: Black thermoplastic PC940. Corrosion and wear protection.<br>Cable: 4.5M black with TPU jacket.<br>With CE and TUV mark issued by TUV.                                                                                                                                                                                              |
| Feature                 | 1. The product complies with the Low Voltage Directive 2014/35/EU, IEC61851-1:2019<br>2.IP67, weatherproof; leakage protection; impact resistance<br>3. Charging status and working error are simply displayed by LED indicator light and LCD screen<br>3. Optional function of current selection button,<br>4.8A-32A free switching current |
| Warranty                | 1 Years for the whole machine                                                                                                                                                                                                                                                                                                                |

#### Advanteages:

Temperature Protection

Efficient Charging

Short Circuit Protection

Protection Level IP66

Built in Smart Chip



## Product details

---



Customizable plug



Customizable



Simple and easy to operate



## EV CHARGING



Easy to carry and charge



Packing list

# Packing list



## Caution:

Don't submerge the EV charging cable in water.

Don't step on, fold or knot the cable.

Don't drop the EV charging box or place a heavy object on it.

Don't place the charging cable near high temperature object when charging.

Don't operate the EVSE in temperatures beyond its operating range of -25°C to 55°C.

Power-supply side input cable should be at least 3\*2.5mm (recommended 3\*4mm), with a standard 16A socket. It is suggested that

the power distribution is done by the professionals.

Don't put fingers into the charging connector when the power plug is still connecting to the power.

Don't use this EV charging box when the cable is damaged.

The EV charging box is only for EV charging using.

Don't use this device with other brand's extension cord or adapter.



**MINKO (SZ) TECHNOLOGY CO., LIMITED**



+8613539872669



yumiko@szminko.com



evstationcharger.com

309 West Lake Industrial Zone, Cuishan Road, Dongxiao Street, Luohu District, SZ